

# Avex® 1641


For installation information please refer to the tooling overview and manuals on our website [www.avdel-global.com](http://www.avdel-global.com).  
 Pour les conditions de pose, merci de vous référer à la description de l'outil et aux manuels disponibles sur notre site Web.  
 Angaben zur Verarbeitung entnehmen Sie bitte der Geräteübersicht und den Betriebsanleitungen auf unserer Website.  
 Per informazioni sull'installazione preghiamo consultare i manuali e la panoramica degli attrezzi sul nostro sito web.  
 Para ver información sobre máquinas de colocación, consulte nuestra página web, apartados visión general de máquinas y manuales.



English	Français	Deutsch	Italiano	Español
Large Flange	Tête large	Flachrundkopf extragroß	Testa larga	Cabeza ancha
Body: Aluminium alloy* (2.5 % Mg) Natural	Corps: Alliage d'aluminium* (2.5% Mg) Brut	Hülse: Aluminium* (2.5 % Mg) Blank	Corpo: Lega di alluminio* (2.5% Mg) Nessuna finitura	Cuerpo: Aluminio* (2.5% Mg) Natural
Stem: Low carbon steel**	Tige: Acier bas carbone**	Dorn: Stahl**	Gambo: Acciaio a basso tenore di carbonio**	Vástago: Acero bajo en carbono**
Zinc coated	Revêtement zingué	Verzinkt	Zincato	Zincado

\*: AA 5052, DIN 1725, AlMg2.5, Werkstoff 3.3523

\*\* : BS3111 Type 0, SAE 1015/1018/1022, DIN 1654, Cq15/Cq22



Ø	Flange Thickness		Flange Diameter		M	B	D	E	lb <sup>f1</sup>	lb <sup>f1</sup>	Part No/ref
	min.	max.	min.	max.							
3/16" (4.8 mm)	.062	.250	.193	.199	.55	.635	.084	.112	345	472	01641-00613
	.125	.366			.67				301		01641-00617
	.187	.437			.74				301		01641-00619
	.250	.500			.80				295		01641-00621
	.500	.781			1.11				320		01641-00631

all dimensions in inches / en pouces / alle Maße in Zoll / in pollici / en pulgadas

1) typical values / valeurs moyennes / typische Werte / Valori tipici / resistencias máximas recomendadas