

Hydro-pneumatic Handtool for Lockbolts

722 Model

Features

- Robust and durable construction
- Cast aluminium tool body
- Designed for heavy duty use over long periods of time
- Wide choice of different nose assemblies to suit the access restrictions of the application

Benefits

- Extremely durable lockbolt tool
- High reliability
- Can be fitted with a collar cropper to remove installed Avdelok® lockbolts

Specifications

Weight (without nose equipment)	5.0 kg (11 lbs)
Pull force @ 5.5 bar	26.7 kN (6000lbf)
Stroke min.	19 mm (0.75ins)
Cycle time	3.0 sec
Air supply pressure	5.4 – 8.5 bar
Free air volume @ 5,1 bar	14.6 litres
Noise level	72 dB(A)
Vibration	< 2.5m/s ²

Placing capability

Avdelok® lockbolts \varnothing 6.4 mm ($\frac{1}{4}$ "") to 9.6 mm ($\frac{3}{8}$ "") and Avbolt® structural blind fasteners \varnothing 4.8 mm ($\frac{3}{16}$ "") to 8.0 mm ($\frac{5}{16}$ "").

For detailed information on placing capability and nose equipment please refer to the tool manual on our website www.avdel-global.com or contact your local Avdel representative.



Dimensions (mm/inch)

